

MINIMUM REQUIREMENTS

1

DISCOVERY
BY SILVERWOLF™

4WD MINIMUM REQUIREMENTS

KIT PART # PK-000041

THE FOLLOWING ITEMS ARE REQUIRED BEFORE THIS KIT CAN BE INSTALLED!

VEHICLE MAKE	MODEL	YEAR START	YEAR END	NOTE
E-Z-GO®	TXT® (48V)	1996	PRESENT	Will not fit 36V Cart
REQUIREMENTS	ITEM			NOTE
VEHICLE CONTROLLER	CURTIS® 1206HB- (Original Stock Controller)			
MOTOR TYPE	DC STOCK 48V MOTOR			
CART STATUS (LIFT KIT)	NON-LIFTED CART w/ STOCK STRAIGHT AXLE			Will not fit Drop Axle
HEAVY DUTY SOLENOID W/ PRE-CHARGE RESISTOR	Heavy Duty Solenoid & Pre-Charge Resistor w/ 400 amp Continuous.			If the Solenoid has a Diode it Must be removed before installing this kit. 
BATTERY	Lead Acid			In New or Good condition
	Lithium Ion w/ a rating of at least	Continuous Discharge 100A	Maximum Discharge 200A (10 seconds)	The Batteries can not have a Nominal state of over 72v.
WHEELS/RIMS	12" or bigger Steel or Aluminum Rims with Center or 4-3 Offset.			Most standard 12: Rims are 3-4 Offset
TIRES	23" or smaller Tires with a 10" or smaller width.			Wider Tires may rub on some Vehicles

The Cart MUST BE in working condition and all components / wiring MUST BE stock OEM components before installing the DISCOVERY 4WD kit. If the Cart has been modified or not working properly this MUST BE repaired before ordering this kit.

© 2024 SilverWolf Vehicles Inc. All rights reserved.